

Caption Assist

CA C3



Caption Assist provides live captioning during livestreams and other events.

Caption Assist

Video Input	HDMI up to 3840 x 2160 @ 24/25/30 fps
Video Output	HDMI up to 3840 x 2160 @ 60 fps
Power Supply	TFP 060 – 100-240VAC 50/60Hz Input
Power Source	19VDC, 4.7A, center positive
Power Indicator	Green LED
Remote Power	2-pole Phoenix-style connector (Euroblock)
Network	LAN port for printing and saving images and third-party remote control
USB	5 USB 3.0 ports, plus one USB B-Micro port
Operating Temperature	Approximately 32° F to 122° F (0° C to 50° C)
Comm Ports	2
Dimensions	1 RU - 19" (W) x 1.75" (H) x 8.2" (D) (48.26 cm x 4.45 cm x 20.8 cm)
Weight	5 lbs. (2.3 kg)
Warranty	Two (2) year, parts and labor
Approvals	CE, FCC, Industry Canada, WEEE, RoHS, CB Scheme, RCM, PSE

Architectural Engineering Specs

CA C3

The CA C3 shall have 5 USB 3.0 Ports.

The CA C3 shall have one USB B-Micro Port.

The CA C3 shall accept HDMI input up to 3820 x 2160 at 24/25/30 fps.

The CA C3 shall output for HDMI at 3820 x 2160 at 60 fps.

The CA C3 shall have a RJ 45 LAN port for network connection.

The CA C3 shall have a 2-pole Phoenix-style connector for remote power.

The CA C3 shall have a power source at 19VDC 4.7A.

The CA C3 shall be housed in a 1 RU enclosure measuring 7.625" (19.37 cm) deep.

The CA C3 shall have dual male DE-9 comm connectors.

The CA C3 shall be covered by a two-year parts and labor warranty.

This product shall be the Williams AV model CA C3.

Domestic Sales

Williams AV
10300 Valley View Rd
Eden Prairie, MN 55344
Ph: 800-328-6190 / 952-943-2252
FAX: 952-943-2174
Email: info@williamsav.com
Web: www.williamsav.com

International Sales

International Sales Department
Williams AV
10300 Valley View Rd
Eden Prairie, MN 55344 USA
Phone: +1 952 943 2252
Fax: +1 952 943 2174
Email: info@williamsav.com
Web: www.williamsav.com