





# IR Solution Comparison

	<b>IR T1</b> 	<b>IR T2</b> 	<b>WIR TX90 DC</b> 	<b>IR+</b> 
Channels	2.3/2.8 MHz	2.3/2.8 or 3.3/3.8 MHz	2.3/2.8 or 3.3/3.8 MHz	2.3/2.8 or 3.3/3.8 MHz
Audio inputs	3.5mm line	3.5mm mic, Phoenix line (balanced/unbal.)	Phoenix line (balanced/unbalanced)	¼"/XLR Mic (Phantom)/ Line (bal./unbal.) Dante Optional.
Energy-efficient LEDs	<b>YES</b>	<b>YES</b>	No	<b>YES</b>
Remote Power/Audio	No (TV power possible)	<b>YES</b> (PoE KT option)	No	<b>YES</b> (also control)
3 <sup>rd</sup> Party Control	No	<b>YES</b> (RS-232)	No	Future
Dante Option	No	No	No	<b>YES</b>
Network control	No	No	No	<b>YES</b>
Wi-Fi Dual Technology	No	No	No	<b>YES</b>
Distributed array	No	No	No	<b>YES</b>
Coverage Area	1001 ft <sup>2</sup> /93 m <sup>2</sup>	18,008 ft <sup>2</sup> /1673 m <sup>2</sup>	29,385.5 ft <sup>2</sup> /2730 m <sup>2</sup>	18,008 -288,000 ft <sup>2</sup> / 1673-26,600 m <sup>2</sup> (1-16 IR E4 emitters)